



DAHUA ip of surface video intercom

VTO2111D-WP

CAMERA

Resolution	1 Mpx
Sensor	CMOS
Sensor size	1/4"
Focal distance	2.2mm
Horizontal viewing angle	105°
Diagonal angle of view	125°
Night vision	Sí
Day / Night	Mechanical
Video compression	H.264

POWER CONSUMPTION

Power mode	DC
Voltage	12V
PoE power	Yes
Type PoE	PoE 802.3af
Standby consumption	less than or equal to 1W
Consumption On	Menor o igual a 10W

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP
IP connection	10M/100Mbps
Wi-Fi	Sí
Tipo de Wi-Fi	IEEE802.11 b / g / n

INPUTS/OUTPUTS

Alarm input	2
RS485	1
Number of controllable doors with relay	1, extendable to 2 with module DEE1010B

SYSTEM (RECORDERS)

Processor	Embedded Micro Processor
Operating system	Embedded LINUX

OPENING

Call elements	Simple button
Proximity reader	MIFARE cards

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	135 x 70.4 x 34.4 mm
Material	Plastic
Net weight	400 g

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Maximum humidity	90%

SPECS AND FEATURES

Technology	IP
Number of homes	1

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Memory slot	SD hasta 32 Gb

