



HIKVISION
HiWatch Series

Minidome ip camera of 2 megapixels and fix lens

HWI-D121H

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
OSD menu	Yes
Privacy mask	Yes
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 1.3Mpx / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 / 320 × 240 (25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	95%

LENS

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox / Safari
Management software	iVMS-4200 / iVMS-5200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.8'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.01Lux

MATERIAL AND DIMENSIONS

Dimensions	82.4 x 111 (Ø) mm
Material	Metal and plastic
Net weight	400 g
Weight with packaging	600 g

DISTANCE DORI

Detect	39 m
Observe	15 m
Recognize	8 m
Identify	4 m

GENERAL INFORMATION

Serie	HiWatch
Technology	IP
Type of camera	Minidome

VIDEO ANALYSIS

Detection type	Basic motion detection (pixel difference)
----------------	--

technical datasheet

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	114°

NIGHT VISION

Night vision distance	30 m
Type of night vision	IR
Wavelength	850 nm

AXES

Motion	2-Axis
--------	---------------

Motion detection	Yes
Video Tamper	Sí

