

## P ▲ R ▲ D O X

### Hybrid panel

### MG5000



#### COMMUNICATION

|                        |                                           |
|------------------------|-------------------------------------------|
| External voice module  | <b>Yes, with VDMP3 module</b>             |
| IP                     | <b>Yes, with IP150 module</b>             |
| GPRS                   | <b>Yes, with PCS module</b>               |
| GSM                    | <b>Yes, with PCS module</b>               |
| RTC                    | <b>Sí</b>                                 |
| Programming            | <b>Installer, teacher and maintenance</b> |
| Expansion bus          | <b>Yes, 4 wires</b>                       |
| Communication with CRA | <b>Sí</b>                                 |
| Mobile Network         | <b>GPRS / GSM (with PCS module)</b>       |

#### ZONES

|                         |                       |
|-------------------------|-----------------------|
| Maximum number of zones | <b>32</b>             |
| Keyboard areas          | <b>15</b>             |
| Wired on-board zones    | <b>2 (4 with ATZ)</b> |
| ATZ (Double zones)      | <b>Sí</b>             |

#### ADDITIONAL FEATURES

|                   |                                          |
|-------------------|------------------------------------------|
| Calendar          | <b>Sí</b>                                |
| Software Update   | <b>Sí</b>                                |
| Mobile app        | <b>INSITE GOLD</b>                       |
| Call notification | <b>Yes, with IP or PCS module (GPRS)</b> |

#### AMBIENT

|                       |                     |
|-----------------------|---------------------|
| Operating temperature | <b>0 °C ~ 50 °C</b> |
| Use                   | <b>Indoor</b>       |

#### GENERAL INFORMATION

|                 |               |
|-----------------|---------------|
| Type of Central | <b>Hybrid</b> |
|-----------------|---------------|

#### POWER CONSUMPTION

|                 |                         |
|-----------------|-------------------------|
| Power mode      | <b>AC</b>               |
| Voltage         | <b>16.5V</b>            |
| Amperage        | <b>1200mA</b>           |
| Battery support | <b>Sí, 12V 4 ~ 7 Ah</b> |

#### PARTITIONS AND MEMORIES

|                     |            |
|---------------------|------------|
| Partitions          | <b>2</b>   |
| User codes          | <b>32</b>  |
| Registration events | <b>256</b> |
| Maximum users       | <b>32</b>  |

#### PROGRAMMABLE OUTPUTS

|                 |           |
|-----------------|-----------|
| Maximum of PGMs | <b>16</b> |
| siren           | <b>Sí</b> |
| Telephone line  | <b>Sí</b> |

#### MATERIAL AND DIMENSIONS

|            |                     |
|------------|---------------------|
| Dimensions | <b>140 x 104 mm</b> |
| Net weight | <b>20 g</b>         |

