


P ▲ R ▲ D O X



wired panel with 8 on-board zones

SP6000

COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
RTC	Sí
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires
Communication with CRA	Sí

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1700mA
Battery support	Sí, 12V 4 ~ 7 Ah

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	256
Maximum users	32

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
Mobile app	INSITE GOLD
Call notification	Yes, with IP or PCS module (GPRS)

CERTIFICATION

Grade	2
Normative	EN50131

ZONES

Maximum number of zones	32
Wired on-board zones	8
ATZ (Double zones)	Sí
Keyboards	15

PROGRAMMABLE OUTPUTS

Board	2
Maximum of PGMs	16
siren	Sí
Telephone line	Sí

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

MATERIAL AND DIMENSIONS

Dimensions	190 x 90 mm
Net weight	20 g

GENERAL INFORMATION

Type of Central	Wired
-----------------	--------------

