



## Modulo de salida de 2 relés MDA2YLT

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-10 °C ~ 50 °C</b> |
| Degree of protection  | <b>IP30</b>           |
| Maximum humidity      | <b>95%</b>            |

### ESPECIFICACIONES TÉCNICAS

|                         |                  |
|-------------------------|------------------|
| Short circuit isolator  | <b>Yes</b>       |
| Activation indicator    | <b>Green led</b> |
| Communication indicator | <b>Red led</b>   |

### MATERIAL AND DIMENSIONS

|              |                           |
|--------------|---------------------------|
| Installation | <b>Waterproof case</b>    |
| Dimensions   | <b>140.5 x 73 x 48 mm</b> |

### CERTIFICATION

|           |                |
|-----------|----------------|
| Normative | <b>EN54-18</b> |
|-----------|----------------|

### POWER CONSUMPTION

|                     |                                |
|---------------------|--------------------------------|
| Voltage             | <b>24V ~ 35V con polaridad</b> |
| Standby consumption | <b>1mA</b>                     |

### SPECS AND FEATURES

|      |                                    |
|------|------------------------------------|
| Type | <b>Modulo de salida de 2 relés</b> |
|------|------------------------------------|

