

**HIKVISION®**

Bullet 4 in 1 (cvi, tvi, ahd and analog) camera of 5 megapixels and fix lens

**DS-2CE16H0T-ITF**

**VIDEO (CAMERAS)**

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| Video Resolution  | <b>5 Megapixels</b>                                    |
| BLC               | <b>Yes</b>                                             |
| 2D-NR             | <b>Yes</b>                                             |
| AGC               | <b>Yes</b>                                             |
| AWB               | <b>Yes</b>                                             |
| WDR               | <b>DWDR</b>                                            |
| Images per second | <b>20fps</b>                                           |
| Video output      | <b>1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS</b> |
| Day / night mode  | <b>Automatic / Manual</b>                              |
| OSD menu          | <b>Yes</b>                                             |
| ATW               | <b>Yes</b>                                             |
| Mirror            | <b>On / Off</b>                                        |

**POWER CONSUMPTION**

|                 |              |
|-----------------|--------------|
| Power mode      | <b>DC</b>    |
| Voltage         | <b>12V</b>   |
| Consumption (w) | <b>4.3W</b>  |
| Amperage        | <b>360mA</b> |

**NIGHT VISION**

|                       |             |
|-----------------------|-------------|
| Night vision distance | <b>20 m</b> |
| Type of night vision  | <b>IR</b>   |
| Smart IR              | <b>Yes</b>  |
| EXIR                  | <b>Yes</b>  |

**GENERAL INFORMATION**

|                |                                          |
|----------------|------------------------------------------|
| Serie          | <b>PRO</b>                               |
| Technology     | <b>4 IN 1 (CVI, TVI, AHD and analog)</b> |
| Type of camera | <b>Bullet</b>                            |

**LENS**

|                |               |
|----------------|---------------|
| Lens Type      | <b>Fix</b>    |
| Focal distance | <b>2.8 mm</b> |
| Angle of View  | <b>85.5°</b>  |

**IMAGE**

|                          |                          |
|--------------------------|--------------------------|
| Sensor                   | <b>CMOS ®</b>            |
| Sensor resolution        | <b>2560 x 1944</b>       |
| Electronic shutter speed | <b>1/25s ~ 1/50,000s</b> |
| Minimum lighting         | <b>0.01Lux</b>           |

**AMBIENT**

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-40 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP67</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>90%</b>            |

**DISTANCE DORI**

|           |             |
|-----------|-------------|
| Detect    | <b>75 m</b> |
| Observe   | <b>29 m</b> |
| Recognize | <b>15 m</b> |
| Identify  | <b>7 m</b>  |

**MATERIAL AND DIMENSIONS**

|            |                         |
|------------|-------------------------|
| Dimensions | <b>58 x 163 x 61 mm</b> |
| Material   | <b>Metal</b>            |
| Net weight | <b>350 g</b>            |

**AXES**

|        |               |
|--------|---------------|
| Motion | <b>3-Axis</b> |
|--------|---------------|

