



## Bullet 4 in 1 (cvi, tvi, ahd and analog) camera of 2 megapixels and fix lens

### HWT-B220-M

#### VIDEO (CAMERAS)

|                  |                                                        |
|------------------|--------------------------------------------------------|
| Video Resolution | <b>2 Megapixels</b>                                    |
| BLC              | <b>Yes</b>                                             |
| 2D-NR            | <b>Yes</b>                                             |
| AGC              | <b>Yes</b>                                             |
| WDR              | <b>DWDR</b>                                            |
| Video output     | <b>1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS</b> |
| Day / night mode | <b>Automatic / Manual</b>                              |
| Mirror           | <b>On / Off</b>                                        |

#### NIGHT VISION

|                       |                           |
|-----------------------|---------------------------|
| Night vision distance | <b>40 m</b>               |
| Type of night vision  | <b>IR</b>                 |
| IR ON/Off             | <b>Automatic / Manual</b> |
| Smart IR              | <b>Yes</b>                |
| EXIR                  | <b>Yes</b>                |

#### IMAGE

|                          |                          |
|--------------------------|--------------------------|
| Sensor                   | <b>CMOS ®</b>            |
| Sensor resolution        | <b>1920 x 1080</b>       |
| Electronic shutter speed | <b>1/25s ~ 1/50,000s</b> |
| Minimum lighting         | <b>0.01Lux</b>           |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-40 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP66</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>90%</b>            |

#### DISTANCE DORI

|           |             |
|-----------|-------------|
| Detect    | <b>47 m</b> |
| Observe   | <b>18 m</b> |
| Recognize | <b>9 m</b>  |
| Identify  | <b>5 m</b>  |

#### LENS

|                           |               |
|---------------------------|---------------|
| Lens Type                 | <b>Fix</b>    |
| Focal distance            | <b>2.8 mm</b> |
| Maximum diaphragm opening | <b>F/1.2</b>  |
| Angle of View             | <b>103°</b>   |
| Filtro IR                 | <b>Sí</b>     |

#### POWER CONSUMPTION

|                 |              |
|-----------------|--------------|
| Power mode      | <b>DC</b>    |
| Voltage         | <b>12V</b>   |
| Consumption (w) | <b>4W</b>    |
| Amperage        | <b>330mA</b> |

#### MATERIAL AND DIMENSIONS

|                       |                               |
|-----------------------|-------------------------------|
| Dimensions            | <b>75.4 x 230.8 x 87.2 mm</b> |
| Material              | <b>Metal</b>                  |
| Net weight            | <b>545 g</b>                  |
| Weight with packaging | <b>700 g</b>                  |

#### GENERAL INFORMATION

|                |                                          |
|----------------|------------------------------------------|
| Serie          | <b>HiWatch</b>                           |
| Technology     | <b>4 IN 1 (CVI, TVI, AHD and analog)</b> |
| Type of camera | <b>Bullet</b>                            |

#### AXES

|        |               |
|--------|---------------|
| Motion | <b>3-Axis</b> |
|--------|---------------|

