



HIKVISION
accessories

Reader indoor-outdoor with
keyboard / card mifare 13.56mhz

DS-K1102AMK

FEATURES

| | |
|-----------------------|------------|
| Integrated controller | No |
| LED indicator | Sí |
| Sound warning | Sí |
| Tamper | Sí |
| Watchdog design | Sí |
| DIP Switch | Yes |

POWER CONSUMPTION

| | |
|-----------------|--------------|
| Power mode | DC |
| Voltage | 12V |
| Consumption (w) | 2W |
| Amperage | 500mA |

MATERIAL AND DIMENSIONS

| | |
|--------------|------------------------------------|
| Installation | Wall |
| Dimensions | 121 x 86.5 x 14 mm |
| Material | ABS plastic + Polycarbonate |
| Net weight | 140 g |

SPECS AND FEATURES

| | |
|--------------|---------------|
| Serie | Hika-P |
| Control type | Reader |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -20 °C ~ 65 °C |
| Degree of protection | IP64 |
| Use | Indoor-outdoor |
| Maximum humidity | 90% |

IDENTIFICATION

| | |
|--------------------------|------------------------|
| Mode | Keyboard / Card |
| Keyboard | Sí |
| Type of card | MIFARE 13.56MHz |
| Maximum reading distance | less than 50 mm |

COMMUNICATION

| | |
|------|------------------------|
| Mode | Wiegand / RS485 |
|------|------------------------|

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

| | |
|----------------|----------------|
| Main processor | 32 bits |
|----------------|----------------|

