



## Wired curtain volumetric detector

6933AMP

### DETECTION

Detector type	<b>Wired</b>
Installation height	<b>2 m ~ 2.5 m</b>
Detection distance	<b>12 m</b>
Coverage	<b>2.8 m x 12 m</b>
Antimasking	<b>Yes</b>
Detection technology	<b>Curtain volumetric</b>

### SENSOR

Type of sensor	<b>PIR, radar and active infrared</b>
Sensitivity adjustment	<b>Interruptores DIP</b>
Double element pyroelectric sensor	<b>Si</b>
Digital temperature compensation	<b>Yes</b>

### AMBIENT

Operating temperature	<b>-20 °C ~ 55 °C</b>
Degree of protection	<b>IP65</b>
Use	<b>Indoor-outdoor</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>9V ~ 15V</b>
Amperage	<b>40mA</b>

### MATERIAL AND DIMENSIONS

Dimensions	<b>44 x 117 x 41 mm</b>
Net weight	<b>95 g</b>
Weight with packaging	<b>135 g</b>

### TECHNICAL SPECIFICATIONS

LED indicators	<b>Yes</b>
LED colors	<b>Verde / Rojo</b>

