



P ▲ R ▲ D O X

Módulo expensor de 8 salidas programables

PGM82

POWER CONSUMPTION

| | |
|-----------------------|------------------|
| Power mode | DC |
| Voltage | 11V ~ 16V |
| Amperage | 315mA |
| Relay voltage output | 24V |
| Relay Amperage output | 4000mA |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|--------------------------|
| Dimensions | 165 x 102 x 25 mm |
| Net weight | 215 g |
| Weight with packaging | 250 g |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -20 °C ~ 50 °C |
| Maximum humidity | 95% |

ADDITIONAL FEATURES

| | |
|------------|--------------------|
| Mobile app | INSITE GOLD |
|------------|--------------------|

GENERAL INFORMATION

| | |
|---------------|--|
| Type | Módulo expensor de 8 salidas programables |
| Compatibility | Spectra / Magellan / EVO |

CERTIFICATION

| | |
|-----------|------------------|
| Normative | EN50130-4 |
|-----------|------------------|

PROGRAMMABLE OUTPUTS

| | |
|-------|----------|
| Board | 8 |
|-------|----------|

TECHNICAL CHARACTERISTICS

| | |
|---------------|------------|
| LED indicator | Yes |
|---------------|------------|

