



Ip of surface / embed video intercom

VTO2201F-P

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.9"
Focal distance	2mm
Horizontal viewing angle	139°
Diagonal angle of view	159°
Night vision	Si
Day / Night	ICR
Video compression	H.265

POWER CONSUMPTION

Power mode	DC
Voltage	12V ~ 24V
Consumption (w)	6W
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af

INPUTS/OUTPUTS

Door sensor	1
Botón de salida	1
Blocking output	1
Alarm output	1

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / P2P / IPv4 / UPnP / SNMP / DNS / DDNS / RTSP / RTP / TCP / UDP
IP connection	10M/100Mbps
ONVIF	Yes

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Si
Led indicator	Si, 3

OPENING

Call elements	Simple button
---------------	---------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK07
Use	Indoor-outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	130 x 96 x 28.5 mm
Net weight	350 g
Weight with packaging	470 g

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Si
Audio compression	G.711A/G.711U/PCM

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

SPECS AND FEATURES

Technology	IP
------------	----

