



2 wires / ip of surface / embed video intercom

VTO2202F-P-S2

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.5"
Focal distance	1.9mm
Horizontal viewing angle	169°
Diagonal angle of view	177°
Night vision	Si
Day / Night	ICR
Video compression	H.265

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	12W
Amperage	1000mA
PoE power	Yes
Type PoE	PoE 802.3af

INPUTS/OUTPUTS

Door sensor	1
Botón de salida	1
Blocking entry	1
Alarm output	1

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	SIP / P2P / IPv4 / UPnP / SNMP / DNS / DDNS / RTSP / RTP / TCP / UDP
IP connection	10M/100Mbps
ONVIF	Yes

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Si
Led indicator	Si, 3

OPENING

Call elements	Simple button
---------------	----------------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK07
Use	Indoor-outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	130 x 96 x 28.5 mm
Net weight	350 g
Weight with packaging	400 g

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Si
Audio compression	G.711u

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

GENERAL INFORMATION

Technology	2 Wires / IP
------------	---------------------

