



HIKVISION®

Minidome ip camera of 4 megapixels and fix lens

DS-2CD2143G2-I

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Yes
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx / 1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Sub stream 2	720P / 640 x 480 / 640 x 360 (1 ~ 25fps)
Anti flap	Yes
Mirror	On / Off

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

IMAGE

Sensor	CMOS ®
Sensor resolution	2688 x 1520
Sensor Size	1/3"
Electronic shutter speed	1/3 ~ 1/1000000s
Minimum lighting	0.005Lux

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S y G
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect / Hik-Central
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

VIDEO ANALYSIS

Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Motion detection	Yes
Video Tamper	Sí
Classification Human / vehicle	Yes

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	95%

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.6
Angle of View	103°

GENERAL INFORMATION

Serie	Acusense
Technology	IP
Type of camera	Minidome

NIGHT VISION

technical datasheet

MATERIAL AND DIMENSIONS

Dimensions	84.7 x 110.8 (Ø) mm
Material	Aluminum and plastic
Net weight	530 g
Weight with packaging	720 g

DISTANCE DORI

Detect	67 m
Observe	26 m
Recognize	13 m
Identify	6 m

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	NAS / Micro SD / Recorder
ANR (Redundant Recording in SD)	Yes

SYSTEM (CAMERAS)

Reset button	Yes
--------------	------------

VISION SYSTEM

Night vision distance	30 m
IR ON/Off	Yes
Wavelength	850 nm

AXES

Motion	3-Axis
--------	---------------

