



AJAX

Wireless panel

HUB2-DC6V-W

ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
Mobile devices	iOS 9.1 or later / Android 4.1 or later
SIM card number	2
LED indicators	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	4.2V ~ 10V
Built in battery	Not
Battery life	± 16 hours
Battery model	6V DC
Input current	2200mA @4.2V DC / 500mA @16V DC
Output current	1500mA

VIA RADIO

Frequency	868mHz
Transmission distance	Up to 2000 m (without obstacles)
Maximum power RF	Class 4 (2W) / 850/900Mhz , Class 2 (1W) / 1800/1900MHz

CERTIFICATION

Grade	2
Normative	EN50131

GENERAL INFORMATION

Type of Central	Wireless
-----------------	-----------------

SABOTAGE

Box tamper	Sí
------------	-----------

MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	White

COMMUNICATION

IP	Sí
GPRS	Sí
Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller

AMBIENT

Operating temperature	5 °C ~ 40 °C
Use	Indoor

ZONES

Maximum number of rooms	50
Maximum number of devices	100

PARTITIONS AND MEMORIES

Maximum users	50
---------------	-----------

PROCESSOR

Operating system	OS Malevich
------------------	--------------------

