technical datasheet





Ip recorder of 4 channel and 12 mpx resolution with 4 PoE ports

NVR2104HS-P-I2

Desk / Rack		Installation	4	PoE ports	
		-		Number of	
260 x 232.7 x 47.6 mm	260	Dimensions	1	ports RJ45	
Metal		Material	10 / 100 Mbps	Velocità RJ45	
860g		Net weight	Android / IOS (Apple)	Mobile	
1860 g	kaging	Weight with packa		devices	
Compact 1U		Chassis	Yes	ONVIF	
	DEO SYSTEM	INTELLIGENT VIDE	Web Browser (ActiveX) / Smartphone App / Smart PSS Software	Remote vision	
Vaa	DEO SYSTEM		802.3af	Type PoE	
Yes		Line crossing	SmartPSS	Software	
Yes		Intrusion	iDMSS / gDMSS	Арр	
Yes		Privacy Mask	iemos, gemos	7.66	
nnels (human / vehicle classification)	Yes, 4 channe	SMD PLUS	NITION	FACE RECOGN	
Yes		Motion	8 faces processed per second	Number of faces	
res		detection		Number of	
		RECORDING	1 channel video face recognition	channels	
		Maximum	r chainler video face recognition	with facial	
12 Mpx		recording		recognition	
•		resolution	Notice of faces not registered in the database	Strange mode	
H.265 / H.264	on	Video compression	database	Search Al	
80Mbps		Bandwidth IP cameras	Up to 8 simultaneous faces	(artificial intelligence)	
12Mpx / 4K / 5Mpx / 4Mpx / 3Mp		Resolutions	Up to 10 databases with 5,000 faces in		
/ 1080P / 720P / D1		Resolutions	total / Allows designating name /	Database	
		AMBIENT	gender / birth date / nationality / address / Identification information can	managment	
-10 °C ~ 55 °C	oraturo		be added to each face image.	·	
	erature	Operating temper	Each database can be applied to video	Database	
Indoor		Use	channels independently.	application	
93%	Maximum humidity		Buzzer / voice prompts / email / snapshot / recording / alarm output /	Actions available	
		STORAGE	PTZ activation	after	
es 1	orted hard drives	Number of suppor		detection	
10 TB		Maximum hard dis	SUMPTION	POWER CONS	
	3138 3120 (01110)	-	DC	Power mode	
3,5 SATA"		Type HDD	53V	Voltage	
PERIMETER PROTECTION		(w) 10W	Consumption		
		Channels	1130mA	· · · · · · · · · · · · · · · · · · ·	
2 channels		number with analytics	HISOHIA	Amperage	

identification

vehicle for line crossing and

intrusion

technical datasheet

Simultaneou cameras in reproduction		1/4		
Playback functions	backwar	e / Stop / Fast forward / Fast d / Rewind / Play by frame / / Backup (cut/file) / Partially enlarge / Audio on/off		
Backup mode		USB		
Búsqueda inteligente		Yes		
VIDEO OUTP	UT			
HDMI Output Number 1				
Number of VGA outputs 1				
Resolution HDMI 4K				
SYSTEM (RECORDERS)				
Processor		Industrial grade integrated processor		
Operating system		Embedded LINUX		
Smart fan		Yes		
GENERAL IN	FORMATION			
Serie		Serie 2		
Technology		IP		

VIDEO

IP Channels

Smart search	Search by classification (Human / Vehicle)
AUDIO	
Audio Inputs	1
Audio Outputs	1
INPUTS/OUTPUTS	
USB 2.0	2

