



**Milesight**

Minidome ip camera of 5 megapixels and fix lens

MS-C5375-PD/J

## VIDEO (CAMERAS)

|                   |   |
|-------------------|---|
| Video Resolution  | <b>5 Megapixels</b>   |
| BLC               | <b>Yes</b>  |
| HLC               | <b>Yes</b>  |
| 3D-NR             | <b>Yes</b>  |
| AGC               | <b>Yes</b>  |
| AWB               | <b>Yes</b>  |
| WDR               | <b>WDR (120 dB)</b>   |
| Images per second | <b>25fps</b>  |
| Video output      | <b>RJ45</b>   |
| Day / night mode  | <b>Automatic / Manual</b>   |
| Privacy mask      | <b>Up to 4 zones</b>  |
| Anti fog system   | <b>Yes</b>  |
| Type of Codex     | <b>CBR / VBR</b>  |
| Bit rate          | <b>16Kbps ~ 16Mbps</b>  |
| Compression       | <b>H.265+ / H.265 / H.264</b>   |
| Main stream       | <b>5Mpx / 3Mpx / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps)</b>              |
| Sub stream        | <b>704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)</b>                |
| Sub stream 2      | <b>1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 (1 ~ 25fps)</b> |
| Watermark         | <b>Yes</b>  |
| Anti flap         | <b>Yes</b>  |

## IMAGE

|                          |                         |
|--------------------------|-------------------------|
| Sensor                   | <b>CMOS ®</b>           |
| Sensor resolution        | <b>2592 x 1944</b>      |
| Sensor Size              | <b>1/2.8"</b>           |
| Electronic shutter speed | <b>1s to 1/100,000s</b> |
| Minimum lighting         | <b>0.005Lux</b>         |
| Ratio S / N              | <b>More than 55dB</b>   |

## LENS

|                |               |
|----------------|---------------|
| Lens Type      | <b>Fix</b>    |
| Focal distance | <b>2.8 mm</b> |

## VIDEO ANALYSIS

|                                |   |
|--------------------------------|---|
| Detection type                 | <b>Analytical with human/vehicle classification in line/area crossing</b> |
| Crossing line                  | <b>Yes</b>  |
| Motion detection               | <b>Yes</b>  |
| Abandoned object               | <b>Yes</b>  |
| Missing object                 | <b>Yes</b>  |
| Video Tamper                   | <b>Sí</b>   |
| Loitering detection            | <b>Sí</b>   |
| Classification Human / vehicle | <b>Yes</b>  |

## AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-40 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP67</b>           |
| Anti vandal           | <b>IK10</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>90%</b>            |

## NETWORK FEATURES

|                       |                                |
|-----------------------|--------------------------------|
| IP connection         | <b>1 RJ45 (10M / 100M)</b>     |
| ONVIF                 | <b>Yes, type S, G, T and Q</b> |
| Management software   | <b>Milesight CMS</b>           |
| IP address filter     | <b>Yes</b>                     |
| Network disconnection | <b>Yes</b>                     |

## DISTANCE DORI

|           |             |
|-----------|-------------|
| Detect    | <b>59 m</b> |
| Observe   | <b>23 m</b> |
| Recognize | <b>12 m</b> |
| Identify  | <b>6 m</b>  |

## GENERAL INFORMATION

|                |                              |
|----------------|------------------------------|
| Serie          | <b>AI Mini Camera Series</b> |
| Technology     | <b>IP</b>                    |
| Type of camera | <b>Minidome</b>              |

## NIGHT VISION

# technical datasheet

|                           |              |
|---------------------------|--------------|
| Maximum diaphragm opening | <b>F/1.6</b> |
| Angle of View             | <b>105°</b>  |

## AUDIO(CAMERAS)

|                     |   |
|---------------------|---|
| Built in microphone | <b>Yes</b>                              |
| Audio compression   | <b>G.711 / G.722 / G.726 / AAC</b>      |
| Sampling frequency  | <b>8 kHz / 16 kHz / 32 kHz / 48 kHz</b> |
| Bit rate            | <b>16 Kbps ~ 256 Kbps</b>               |

## POWER CONSUMPTION

|                 |                    |
|-----------------|--------------------|
| Consumption (w) | <b>5.8W</b>        |
| PoE power       | <b>Yes</b>         |
| Type PoE        | <b>PoE 802.3af</b> |

## MATERIAL AND DIMENSIONS

|                       |                          |
|-----------------------|--------------------------|
| Dimensions            | <b>96.5 x 108 (Ø) mm</b> |
| Net weight            | <b>600 g</b>             |
| Weight with packaging | <b>730 g</b>             |

## AXES

|        |               |
|--------|---------------|
| Motion | <b>3-Axis</b> |
|--------|---------------|

|                       |             |
|-----------------------|-------------|
| Night vision distance | <b>25 m</b> |
| Type of night vision  | <b>IR</b>   |
| Starlight             | <b>Yes</b>  |

## STORAGE

|                                 |                                  |
|---------------------------------|----------------------------------|
| MicroSD-Card                    | <b>Up to 256Gb</b>               |
| Storage Systems                 | <b>NAS / Micro SD / Recorder</b> |
| ANR (Redundant Recording in SD) | <b>Yes</b>                       |

