

A-CCTV

26 ports switch with 24 PoE ports

A-SWITCH-2624POE-250



POWER CONSUMPTION

| | |
|------------------------------------|--------------------|
| Power mode | AC |
| Voltage | 100V ~ 240V |
| Amperage | 4100mA |
| Standby consumption | 20W |
| Consumption On | 250W |
| Maximum consumption per port (PoE) | 30W |
| Total maximum consumption (PoE) | 250W |

ETHERNET PORTS

| | |
|--------------------------|--------------------|
| POE ports | 24 |
| Uplink ports | 2 |
| 10 / 100 Base-TX | 24 |
| POE Ports Speed | 10 / 100 |
| Uplink ports speed | 10/100/1000 |
| Number of Ethernet ports | 26 |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|--------------------------|
| Installation | Desk / Rack |
| Dimensions | 330 x 204 x 44 mm |
| Material | Metal |
| Net weight | 2300 g |
| Weight with packaging | 3000 g |

SYSTEM (SWITCH)

| | |
|-------------------|------------|
| MAC address table | 16K |
|-------------------|------------|

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -20 °C ~ 55 °C |
| Degree of protection | IP30 |
| Use | Indoor |
| Maximum humidity | 90% |
| Lightning protection | 4KV |

CHARACTERISTICS (SWITCH)

| | |
|-------------------------------|------------------|
| Data rate supported | 14.8 Gbps |
| Maximum transmission distance | 250 m |
| Buffer Memory | 4 Mb |

NET STANDARD

| | |
|-------------|------------|
| IEEE802,3af | Yes |
| IEEE802,3at | Yes |

