## technical datasheet





Ip recorder of 16 channel and 12 mpx resolution with 16 PoE ports

NVR2216-16P-I

NETWORK FEATUR	RES	FACE RECOC	INITION	
PoE ports	16	Number of	8 faces processed per second	
Number of	1	faces Number of		
ports RJ45	10 /100 /1000 Mb	channels	1 channel video face recognition	
Velocità RJ45	10 / 100 / 1000 Mbps	with facial recognition		
Mobile devices	Android / IOS (Apple)	Strange	Notice of faces not registered in the	
ONVIF	Yes	mode	database	
Remote <b>W</b> e	eb Browser (ActiveX) / Smartphone App / Smart PSS Software	Search Al (artificial intelligence)	Up to 8 simultaneous faces	
Type PoE	802.3af	intelligence)	Up to 10 databases with 5,000 faces in total / Allows designating name / gender / birth date / nationality / address / Identification information can be added to each face image.	
PoE consumption	25.5W per port / 130W in total	Database managment		
Арр	iDMSS / gDMSS	managment		
RECORDING		Database application	Each database can be applied to video channels independently.	
Maximum recording	12 Mpx	Actions available	ns Buzzer / voice prompts / email /	
resolution	<u> </u>	after		
Input bandwidth	200Mbps	detection	P12 activation	
Video compression	H.265 / H.264	POWER CON	ISUMPTION	
Recording mode	Manual / Programmed / Motion Detection / Alarm	Power mode	AC	
Audio compression	C 711A / C 711U / C 726 / AAC /	Voltage	100V ~ 240V	
——————————————————————————————————————	РСМ	Consumption	n (w) 10W	
Resolutions	12Mpx / 4K / 5Mpx / 4Mpx / 3Mpx / 1080P / 720P / D1	 Amperage	3500mA	
Output bandwidth	100Mbps	REPRODUCT	ION AND COPY OF SECURITY	
MATERIAL AND DII	MENSIONS	Simultaneou	1/4/8/9/16	
Installation	Desk / Rack	cameras in reproduction		
Dimensions	375 x 329.3 x 53 mm	reproduction	Play / Pause / Stop / Fast forward / Fast	
Material	Metal	Playback functions	backward / Rewind / Play by frame / Full screen / Backup (cut/file) / Partially	
Net weight	2650 g		enlarge / Audio on/off	
Weight with packag	ging <b>3910 g</b>	Backup mode	USB	
Chassis	1U	Synchronized		
		playback	16	
AMBIENT		\/ DEQ QUES	UT	
Operating tempera	ture -10 °C ~ 55 °C	VIDEO OUTPUT		
Use	Indoor	HDMI Output Number 1		
Maximum humidity	93%	Number of VGA outputs 1		
STORAGE		Resolution H	DMI 4K	

## technical datasheet

		Irives 2	Number of supported
Alarm input 4		it) 8 TB	Maximum hard disk si
USB 2.0 <b>2</b>		<u> </u>	
Alarm output 2		3,5 SATA"	Type HDD
			PERIMETER PROTECT
GENERAL INFORMATION			Channels
Serie Wiz Sense		2 channels	number with
IP	Technology		analytics
"	reermenegy	n secondary recognition /	Type of
	AUDIO	hicle for line crossing and intrusion	identification
Audio Inputs 1		by classification (Human /	Smart search
1	Audio Outputs	Vehicle)	SITIAIT SEAICII
			VIDEO
EO SYSTEM	INTELLIGENT VIDE	16	IP Channels
Yes	Face	16	
	detection	12 Megapíxeles	Resolution IP cameras
Yes, 4 channels (human / vehicle	SMD PLUS		
classification)			SYSTEM (RECORDERS
		ndustrial grade integrated processor	Processor
		Embedded LINUX	Operating
			system

