



## Wired curtain volumetric adjustable up to 220 m detector

CH10100001



### DETECTION

Detector type	<b>Wired</b>
Installation height	<b>2.5 m ~ 4 m</b>
Angle detection	<b>1.3°</b>
Detection distance	<b>Adjustable up to 220 m</b>
Coverage	<b>220 m x 5.1 m</b>
Detection speed	<b>1 m/s ~ 3 m/s</b>
Antimasking	<b>Yes</b>
PIR detection advance at ground level (PIR Creep)	<b>Si</b>
Detection technology	<b>Curtain volumetric</b>
360PROtect™	<b>Yes</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>10.5V ~ 30V</b>
Amperage	<b>20mA</b>

### CERTIFICATION

Grade	<b>3</b>
Normative	<b>EN50131</b>
Environmental class	<b>IV</b>

### SENSOR

Type of sensor	<b>PIR</b>
Sensitivity adjustment	<b>Si</b>

### MATERIAL AND DIMENSIONS

Installation	<b>Wall / Post</b>
Dimensions	<b>358 x 188 x 290 mm</b>
Material	<b>Asa</b>
Net weight	<b>1070 g</b>
Weight with packaging	<b>2000 g</b>

### AMBIENT

Operating temperature	<b>-40 °C ~ 60 °C</b>
Degree of protection	<b>IP65</b>
Use	<b>Indoor-outdoor</b>

### TECHNICAL SPECIFICATIONS

LED indicators	<b>Yes</b>
Tamper	<b>Yes</b>

### GENERAL INFORMATION

Serie	<b>ADPRO® PRO E</b>
-------	---------------------

