



## Wired volumetric detector

FLX-S-DT-X5

### DETECTION

|                      |                                                               |
|----------------------|---------------------------------------------------------------|
| Detector type        | <b>Wired</b>                                                  |
| Detection distance   | <b>12 m / 18 m (depending on wide / narrow configuration)</b> |
| Angle detection      | <b>85° / 5° (according to wide / narrow configuration)</b>    |
| Installation height  | <b>2 m ~ 3 m</b>                                              |
| Pets immunity        | <b>Sí</b>                                                     |
| Alarm period         | <b>2.0 s ± 0.5 s</b>                                          |
| Detection technology | <b>Volumetric</b>                                             |

### SENSOR

|                                  |                                                                          |
|----------------------------------|--------------------------------------------------------------------------|
| Type of sensor                   | <b>PIR and microwave (wide mode) / PIR (narrow mode)</b>                 |
| Sensitivity adjustment           | <b>Interruptores DIP</b>                                                 |
| Digital temperature compensation | <b>Sí</b>                                                                |
| Operating modes                  | <b>Wide beam / Narrow beam depending on lens position and DIP Switch</b> |

### MATERIAL AND DIMENSIONS

|                       |                         |
|-----------------------|-------------------------|
| Dimensions            | <b>130 x 62 x 56 mm</b> |
| Net weight            | <b>90 g</b>             |
| Weight with packaging | <b>135 g</b>            |

### CERTIFICATION

|       |          |
|-------|----------|
| Grade | <b>2</b> |
|-------|----------|

### POWER CONSUMPTION

|            |                   |
|------------|-------------------|
| Power mode | <b>DC</b>         |
| Voltage    | <b>9.5V ~ 16V</b> |
| Amperage   | <b>15mA</b>       |

### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-20 °C ~ 50 °C</b> |
| Use                   | <b>Indoor</b>         |
| Maximum humidity      | <b>95%</b>            |

### ESPECIFICACIONES TÉCNICAS

|                |           |
|----------------|-----------|
| LED indicators | <b>Sí</b> |
| Tamper         | <b>Sí</b> |

