

HIKVISION®

Ip recorder of 16 channel and 12
mpx resolution with 16 PoE
ports

DS-7616NXI-I2/16P/S**NETWORK FEATURES**

PoE ports	16
Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Type PoE	802.3at / af
PoE consumption	200W
Software	IVMS
App	Hik-Connect

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Number of BNC outputs	1
Resolution HDMI	4K
Resolución VGA	1080P
Resolution BNC	704 x 576
Independent video signals	Yes

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	1
USB 3.0	1
Alarm output	1

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Audio compression	G.711A / G.711U / G.722 / G.726 / MP2L2
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	256Mbps

MATERIAL AND DIMENSIONS

Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	3000 g
Weight with packaging	3600 g
Chassis	1U

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	15W

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

INTELLIGENT VIDEO SYSTEM

POS	Yes
VCA	Sí
Motion detection	Yes

REPRODUCTION AND COPY OF SECURITY

Búsqueda inteligente	Yes
Synchronized playback	16

FACE RECOGNITION

technical datasheet

SPECS AND FEATURES

Technology	IP
Serie	PRO

PERIMETER PROTECTION

Channels number with analytics	4 channels / 12 IVS rules for each channel
Type of identification	Human secondary recognition / vehicle for line crossing and intrusion

VIDEO

IP Channels	16
-------------	----

Number of faces	4 faces processed per second
Database managment	Up to 16 databases with 10,000 faces in total / Allows designating name / gender / birth date / nationality / address / Identification information can be added to each face image

