



## Conventional siren WCW98



### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 55 °C |
| Degree of protection  | IP65           |
| Use                   | Outdoor        |
| Maximum humidity      | 95%            |

### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Dimensions            | 121 x 109 x 63 mm |
| Material              | ABS plastic       |
| Net weight            | 260 g             |
| Weight with packaging | 290 g             |

### TECHNICAL SPECIFICATIONS

|              |               |
|--------------|---------------|
| Tone         | 32            |
| VAD coverage | W-3-7 / W-4-9 |

### GENERAL INFORMATION

|      |                    |
|------|--------------------|
| Type | Conventional siren |
|------|--------------------|

### POWER CONSUMPTION

|                   |          |
|-------------------|----------|
| Power mode        | DC       |
| Voltage           | 9V ~ 60V |
| Alarm Consumption | 14.5mA   |

### TECHNICAL CHARACTERISTICS

|               |                              |
|---------------|------------------------------|
| LED indicator | Yes, VAD coverage selectable |
| Sound output  | 98dB ~ 105dB                 |

### CERTIFICATION

|           |         |
|-----------|---------|
| Normative | EN54-23 |
|-----------|---------|

