



**● detnov**  
**monoxide central**  
**CMD-501**

## TECHNICAL CHARACTERISTICS (MONOXIDE)

Measurement scale	<b>0 to 300 ppm CO</b>
Zone max distance	<b>2 km with 1.5 mm<sup>2</sup> cable</b>
Extraction levels	<b>Programmable from 0 to 299 ppm</b>
Alarm levels	<b>Programable de 0 a 299 ppm</b>
Operating modes	<b>Automatic by maximum / Automatic by average / OFF/ON</b>
Indication of concentration by area	<b>Yes</b>
Low power mode	<b>Yes</b>

## AMBIENT

Operating temperature	<b>-5 °C ~ 40 °C</b>
Degree of protection	<b>IP30</b>
Use	<b>Indoor</b>
Maximum humidity	<b>95%</b>

## ZONAS (INCENDIO)

Maximum number of zones	<b>1</b>
Maximum number of detectors per zone	<b>32</b>

## GENERAL INFORMATION

Type of Central	<b>Monoxide</b>
-----------------	-----------------

## POWER CONSUMPTION

Power mode	<b>AC</b>
Voltage	<b>90V ~ 264V</b>
Consumption (w)	<b>45W</b>

## MATERIAL AND DIMENSIONS

Dimensions	<b>439 x 268 x 112 mm</b>
Net weight	<b>1780 g</b>
Weight with packaging	<b>2400 g</b>

## SALIDAS (INCENDIO)

Alarm relay	<b>1</b>
Relé de extracción	<b>2</b>

## CERTIFICATION

Normative	<b>UNE 23300</b>
-----------	------------------

