



HIKVISION
accessories

Ip video door station with camera

DS-KD8003-IME1/Flush

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	4W
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Installation	Embed
Dimensions	98 x 99.8 x 43.9 mm
Net weight	350 g
Weight with packaging	760 g
Faceplate measurements	134 x 124 x 4 mm

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Door sensor	2
Exit button	2

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	180°
Day / Night	ICR
Video compression	H.264

CAPACITY

Register	2000
Linked gates	500

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Degree of protection	IP65
Use	Indoor-outdoor
Maximum humidity	95%

SYSTEM (RECORDERS)

Processor	Embedded MCU Processor
Operating system	Embedded LINUX
Flash	16 MB
RAM	256 MB

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Audio compression	G.711u

GENERAL INFORMATION

Technology	IP
Type	IP Video Door Station with camera

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / RSTP
IP connection	10 / 100Mbps autoadaptive

OPENING

Call elements	Simple button
---------------	----------------------

