

HIKVISION®**Ip recorder of 16 channel and 12 mpx resolution****DS-7616NXI-K2****NETWORK FEATURES**

Number of ports RJ45	1
Speed RJ45	10 / 100 / 1000 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Software	IVMS
App	Hik-Connect

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	385 x 315 x 52 mm
Material	Metal
Net weight	1720 g
Weight with packaging	2810 g
Chassis	1U

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
VGA resolution	1080P
Independent video signals	Yes

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	2
Alarm output	1

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

VIDEO

IP Channels	16
-------------	----

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Audio compression	G.711A / G.711U / G.722 / G.726 / AAC
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	160Mbps

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	15W
Amperage	3300mA

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

GENERAL INFORMATION

Serie	Acusense
Technology	IP

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle	Yes
Motion detection	Yes, 2.0

REPRODUCTION AND COPY OF SECURITY

Synchronized playback	16
-----------------------	----

Resolution IP cameras

12 Megapíxeles

FACE RECOGNITION

Number of channels with facial recognition **1 channel video face recognition / 4 channels facial photo recognition**

Database managment **Up to 16 databases with 20,000 faces in total**

PERIMETER PROTECTION

Channels number with analytics

2 channels

