



**HIKVISION**  
accessories

## IP video intercom for surface

**DS-KV6113-WPE1**

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>10W</b>
Amperage	<b>850mA</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

### INPUTS/OUTPUTS

Alarm input	<b>4</b>
RS485	<b>1</b>
Door sensor	<b>1</b>
Exit button	<b>1</b>
Relay NO/NC	<b>1</b>

### AMBIENT

Operating temperature	<b>-40 °C ~ 55 °C</b>
Degree of protection	<b>IP65</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>

### SYSTEM (RECORDERS)

Processor	<b>Embedded MCU Processor</b>
Operating system	<b>Embedded LINUX</b>
RAM	<b>256 MB</b>
ROM	<b>32 MB</b>

### AUDIO (VIDEO INTERCOM)

Sound input	<b>Omni-directional microphone</b>
Sound output	<b>Built-in speaker</b>
Audio compression	<b>G.711u</b>

### OPENING

Call elements	<b>Simple button</b>
Proximity reader	<b>MIFARE cards</b>

### CAMERA

Resolution	<b>2 Mpx</b>
Horizontal viewing angle	<b>131°</b>
Night vision	<b>Si</b>
Day / Night	<b>IR</b>
Video compression	<b>H.264</b>

### MATERIAL AND DIMENSIONS

Installation	<b>Surface</b>
Dimensions	<b>138 x 65 x 27 mm</b>
Net weight	<b>195 g</b>
Weight with packaging	<b>385 g</b>

### IDENTIFICATION

Type of card	<b>MIFARE 13.56MHz</b>
Number of cards	<b>10000</b>
Number of users	<b>2000</b>

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	<b>TCP / IP / RSTP</b>
IP connection	<b>10 / 100Mbps autoadaptive</b>
Wi-Fi	<b>Si</b>

### GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	<b>Si</b>
Led indicator	<b>Yes, 2</b>

### GENERAL INFORMATION

Technology	<b>IP</b>
------------	-----------

