

HIKVISION
HiWatch Series



Bullet ip camera of 2 megapixels and optical zoom lens

HWI-B620H-Z

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Yes
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Live view	Up to 6 channels
IP address filter	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.005Lux

DISTANCE DORI

Detect (Open lens)	46 m
Detect (Closed Lens)	122 m
Observe (Open lens)	18 m
Observe (Closed lens)	49 m
Recognize (Open lens)	9 m
Recognize (Closed lens)	24 m
Identify (Open lens)	5 m
Identify (Closed lens)	12 m

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	11W
Amperage	900mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Optical zoom
Focal distance	2.8 mm ~ 12 mm
Maximum diaphragm opening	F/1.6
Angle of View	95° ~ 36°
Filtro IR	Sí

NIGHT VISION

Night vision distance	50 m
Type of night vision	IR
EXIR	Yes
Wavelength	850 nm

GENERAL INFORMATION

Serie	HiWatch
Technology	IP
Type of camera	Bullet

VIDEO ANALYSIS

Detection type	Basic motion detection (pixel difference)
----------------	--

technical datasheet

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	244.4 x 105 (Ø) mm
Material	Metal
Net weight	700 g
Weight with packaging	955 g

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	FTP / Micro SD

SYSTEM (CAMERAS)

Reset button	Yes
--------------	------------

Motion detection	Yes
Video Tamper	Sí

AXES

Motion	3-Axis
--------	---------------

