technical datasheet





5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 8 channel and 1 mpx maximum resolution

HWD-5108MH-G4

RECORDING		NETWORK FEATURES	
Maximum recording	1 Mpx	Number of ports RJ45	1
resolution	ТМРХ	Speed RJ45	10 / 100 Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264	Maximum	<u>-</u>
Resolution HDCVI	1 Megapixel (720P)	number of users	64
recording Resolution HDTVI		Mobile devices	Android / IOS (Apple)
recording	1 Megapixel (720p)	Remote vision Web	Browser / Smartphone App and Hik-Connect Software.
Resolution recording AHD	1 Megapixel (720p)	Software	IVMS
lmages per second Main stream	1080P Lite / 720P Lite / WD1 / 4CIF / VGA / CIF (1 ~15fps)	Арр	Hik-Connect
Images per second Extra stream	CIF / QVGA (1 ~ 15fps)	MATERIAL AND DIMENSIONS	
Video bit rate	32 Kbps ~ 4 Mbps	Installation	Desk / Rack
Audio compression	G.711U	Dimensions	260 x 222 x 45 mm
Speed audio bits	64Kbps per channel	Material	Metal
	o straipe per estationer	Net weight	850 g
VIDEO		Weight with packaging	1340 g
BNC channels	8	DOWED CONCUMENTAL	
IP Channels	10, replacing the BNC channels	POWER CONSUMPTION Power mode	DC
Accepted IP cameras	8 BNC cameras + 2 IP camera	Voltage	12V
Admitted resolutions	1080P / 720P	Consumption (w)	17W
Admitted resolutions	1080P / 720P	Amperage	1500mA
Admitted resolutions	1080P / 720P	AMBIENT	
AHD	1060P / 720P	Operating temperature	-10 °C ~ 55 °C
Cameras CVBS	Yes	Use	Indoor
Resolution IP cameras	5 Megapíxeles	Maximum humidity	90%
VIDEO OUTPUT		AUDIO	
HDMI Output Number	1	Audio Inputs	1
Number of VGA outputs	<u> </u>	Audio Outputs	1
Resolution HDMI	1080P	·	
VGA resolution	1080P	INPUTS/OUTPUTS	
Similar video signals	HDMI and VGA	USB 2.0	2
GENERAL INFORMATIO	DN	REPRODUCTION AND CO	PY OF SECURITY
		Synchronized playback	8
	O-CVI, HD-TVI, AHD, analog and		
	IP)		

technical datasheet

Compatibility Hikvision HA series cameras

STORAGE

Number of supported hard drives 1

Maximum hard disk size (Unit) 4 TB

Type HDD 3,5 SATA"

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle

Yes 20 on all analogue



