



HIKVISION
HiWatch Series

Minidome ip camera of 2 megapixels and fix lens

HWI-D129HA

VIDEO (CAMERAS)

Resolución vídeo	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Resolución sensor	1920 x 1080
Sensor Size	1/2.8"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.001Lux
Ratio S / N	Más de 52dB

NIGHT VISION

Night vision distance	30 m
Tipo de visión nocturna	Luz blanca
IR ON/Off	Automatic / Manual
Full Color	Yes
White light	Sí

AMBIENT

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0
Angle of View	106°
Minimum focus distance	1500mm

DISTANCE DORI

Detect	42 m
Observe	17 m
Recognize	8 m
Identify	4 m

VIDEO ANALYSIS

Tipo de deteccion	Detección avanzada (clasificación persona/vehículo)
Video Tamper	Sí
Classification	Sí
Human / vehicle	

technical datasheet

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	95%

MATERIAL AND DIMENSIONS

Dimensions	97.6 x 121.5 (Ø) mm
Material	Aluminum and plastic
Net weight	500 g
Weight with packaging	700 g

AXES

Motion	3-Axis
--------	---------------

Motion detection 2.0	Yes (human and vehicle)
-------------------------	--------------------------------

SPECS AND FEATURES

Technology	IP
Type of camera	Minidome
Serie	ColorVu

STORAGE

Storage Systems	FTP
-----------------	------------

