



5 ports cloud switch with 4 PoE ports

DS-3E1105P-EI

REMOTE MANAGEMENT

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

CHARACTERISTICS (SWITCH)

Data rate supported	10 Gbps
Packet redirection speed	7.44 Mpps
VLAN	802.1Q
DHCP	Sí
Maximum transmission distance	300 m
Buffer Memory	1 Mb
Mirror port	Sí
PoE Watchdog	Yes

MATERIAL AND DIMENSIONS

Installation	Desk / wall
Dimensions	121.1 x 83.1 x 27.6 mm
Material	Metal
Net weight	200 g
Weight with packaging	750 g

NET STANDARD

IEEE802.3af	Sí
IEEE802.3at	Sí

POWER CONSUMPTION

Power mode	DC
Voltage	54V
Consumption (w)	65W
Amperage	1200mA
Standby consumption	≤ 0.9W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	60W

ETHERNET PORTS

POE ports	4
Puertos Uplink	1
POE Ports Speed	10 / 100
Uplink ports speed	10 / 100
Number of Ethernet ports	5
Puertos PoE prioritarios	2 (priorizados en caso de congestión)

AMBIENT

Operating temperature	0 °C ~ 40 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

SYSTEM (SWITCH)

MAC address table	2K
-------------------	-----------

