



Milesight

**Ptz ip camera of 5 megapixels
and optical zoom lens**

MS-C5341-X25PE

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Digital Zoom	16x
Privacy mask	Up to 8 zones
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	16Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Main stream	5Mpx / 3Mpx / 1080P / 1.3Mpx / 720P / 704 x 576 (1 ~ 25fps)
Sub stream	704 x 576 / 640 x 480 / 640 x 360 / 352 x 288 / 320 x 240 (1 ~ 25fps)
Sub stream 2	1080P / 720P / 704 x 576 / 640 x 480 / 640 x 360 / 320 x 240 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes

LENS

Lens Type	Optical zoom
Optical zoom	25x
Focal distance	4.8 mm ~ 120 mm
Maximum diaphragm opening	F/1.5 ~ F/3.5
Angle of View	57° ~ 2.8°
Minimum focus distance	100mm ~ 1500mm
Autofocus	Yes
Zoom speed	6 s

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Funciones IA	Conteo de personas, detección facial con metadatos
Auto tracking	Yes
Crossing line	Yes
Face detection	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Video Tamper	Sí
Loitering detection	Sí
Classification Human / vehicle	Yes
People and objects counting	Yes

DISTANCE DORI

Detect (Open lens)	104 m
Detect (Closed Lens)	2122 m
Observe (Open lens)	41 m
Observe (Closed lens)	842 m
Recognize (Open lens)	21 m
Recognize (Closed lens)	424 m
Identify (Open lens)	10 m
Identify (Closed lens)	212 m

IMAGE

Sensor	CMOS ®
Sensor resolution	2592 x 1944
Sensor Size	1/2.8'
Electronic shutter speed	1s to 1/100,000s
Minimum lighting	0.008 Lux
Ratio S / N	More than 55dB

AUDIO(CAMERAS)

technical datasheet

PTZ

Pan / Tilt Range	Horizontal 360° / Vertical -5 ~ 90° with autoflip
Manual speed control	Horizontal 0.1°/s ~ 250°/s / Vertical 0.1°/s ~ 160°/s
Speed between presets	Horizontal 250°/s / Vertical 160°/s
Memories	300
PTZ mode	8 Tour between established points, 4 rounds
Position after power failure	Return to the position before the fault
Idle mode	Auto Scan / Auto Home / Preset Freezing / 3D Positioning / PTZ Limits / Initial Position
RS485	1 Input

POWER CONSUMPTION

Power mode	AC
Voltage	24V
Consumption (w)	27W
Amperage	3000mA
PoE power	Yes
Type PoE	PoE+ 802.3at

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP66
Use	Indoor-outdoor
Maximum humidity	95%
Lightning protection	6KV

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S, G, T and Q
Management software	Milesight CMS
IP address filter	Yes
Network disconnection	Yes

GENERAL INFORMATION

Serie	AI PTZ Camera Series
Technology	IP
Type of camera	PTZ

INPUTS/OUTPUTS (CAMERAS)

Alarm	4 Inputs/ 2 Outputs
-------	---------------------

Audio input	1 Input
Audio compression	G.711 / G.722 / G.726 / AAC
Sampling frequency	8 kHz 16 kHz 32 kHz 44.1 kHz 48 kHz
Bit rate	16 Kbps ~ 256 Kbps
Audio output	1

MATERIAL AND DIMENSIONS

Dimensions	308 x 205 (Ø) mm
Material	Metal
Net weight	4000 g
Weight with packaging	5620 g
Support included	Yes

NIGHT VISION

Night vision distance	200 m
Type of night vision	IR
IR ON/Off	Automatic / Manual
Starlight	Yes

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	NAS / FTP / Micro SD
Storage anomaly	Yes
ANR (Redundant Recording in SD)	Yes

AXES

Motion	3-Axis
--------	--------

METADATA

Face	Gender / age / glasses / beard / mask
------	---------------------------------------

