



HIKVISION
HiWatch Series

Minidome ip camera of 2 megapixels and fix lens

HWI-T220HA-LU

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.9"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.005Lux
Ratio S / N	Más de 52dB

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
White light	Sí
Wavelength	850 nm
Smart Hybrid Light	Yes (switches from IR to colour with human detection)

AUDIO(CAMERAS)

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.6
Angle of View	103°
Filtro IR	Sí

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

DISTANCE DORI

Detect	45 m
Observe	18 m
Recognize	9 m
Identify	4 m

GENERAL INFORMATION

technical datasheet

Built in microphone	Yes
Audio compression	G.711A / G.711U / G.722.1 / G.726 / AAC-LC / MP2L2 / PCM
Noise filter	SI
Sampling frequency	8kHz / 16kHz
Bit rate	64 Kbps (G.711A / G.711U) / 16 Kbps (G.722.1 / G.726) / 16 ~ 64 Kbps (AAC-LC) / 32 ~ 160 Kbps (MP212)

MATERIAL AND DIMENSIONS

Dimensions	89.2 x 110 (Ø) mm
Material	Metal and plastic
Net weight	340 g
Weight with packaging	560 g

VIDEO ANALYSIS

Detection type	Advanced detection (person/vehicle classification)
Motion detection	Yes
Video Tamper	Yes
Classification Human / vehicle	Yes

STORAGE

Storage Systems	FTP
-----------------	-----

Serie	HiWatch
Technology	IP
Type of camera	Minidome
AXES	
Motion	3-Axis

