

## DAVANTIS

### 26-channel analytics server

#### DF26



#### DETECTION OF VIDEO AND ALARM

Personas	<b>Yes</b>
Vehículos	<b>Yes</b>
Entrada/salida de región	<b>Yes</b>
Sabotaje	<b>Yes</b>
Merodeo	<b>Yes</b>
Objeto abandonado/perdido	<b>Yes</b>
Permite combinar reglas	<b>Yes</b>
Definición de niveles de seguridad	<b>Yes</b>

#### MATERIAL AND DIMENSIONS

Installation	<b>Enrackable</b>
Dimensions	<b>482 x 300 x 90 mm</b>
Material	<b>Metal</b>
Net weight	<b>8000 g</b>
Chassis	<b>2U</b>

#### POWER CONSUMPTION

Power mode	<b>AC</b>
Voltage	<b>100V ~ 240V</b>
Consumption (w)	<b>130W</b>
Power supply included	<b>Yes</b>

#### VIDEO

ONVIF	<b>Yes</b>
ONVIF bridge	<b>Yes</b>
Canales de analítica	<b>26</b>
Soporta cámaras térmicas	<b>Yes</b>

#### DETECTION DISTANCE (DAY/NIGHT)

Calculations based on	<b>Cameras installed at 4 m height with 1/3" sensor</b>
3 mm lens	<b>32 m (blind distance: 2 m)</b>
8 mm lens	<b>67 m (blind distance: 8 m)</b>
15 mm lens	<b>70 m (blind distance: 14 m)</b>

#### DETECTION DISTANCE (THERMAL)

Cálculos basados en	<b>Cameras installed at 4 m height with 384 x 288 sensor</b>
Óptica de 7 mm	<b>70 m (distancia ciega: 7 m)</b>
Óptica de 10 mm	<b>100 m (distancia ciega: 11 m)</b>
15 mm lens	<b>155 m (blind distance: 17 m)</b>
Óptica de 25 mm	<b>245 m (distancia ciega: 29 m)</b>

#### COMMUNICATION

Communication with CRA	<b>Yes</b>
Comunicación con VMS	<b>Yes</b>
Comunicación con PSIM	<b>Yes</b>
Mobile app	<b>Davantis</b>

#### OUTPUTS

HDMI	<b>1</b>
VGA	<b>2</b>
Headphone jack	<b>1</b>
RJ45	<b>1 x 10/100/1000</b>

#### AMBIENT

Operating temperature	<b>-10 °C ~ 35 °C</b>
Use	<b>Indoor</b>
Maximum humidity	<b>90%</b>

#### INPUTS

USB	<b>4 x USB 2.0 / 2 x USB 3.0</b>
-----	----------------------------------