



## MOVOK

Minidome ip camera of 5 megapixels and fix lens

VK-IPC-T351-AS-I

### VIDEO (CAMERAS)

Resolución vídeo	<b>5 Megapixels</b>
BLC	<b>Yes</b>
HLC	<b>Yes</b>
3D-NR	<b>Yes</b>
AGC	<b>Yes</b>
AWB	<b>Yes</b>
WDR	<b>WDR (140 dB)</b>
Images per second	<b>25fps</b>
Video output	<b>RJ45</b>
Day / night mode	<b>Colour</b>
Privacy mask	<b>Up to 4 zones</b>
Type of Codex	<b>CBR / VBR</b>
Bit rate	<b>3Kbps ~ 20480Kbps</b>
Compression	<b>H.265 / H.264</b>
Main stream	<b>5Mpx (1 ~ 25fps)</b>
Sub stream	<b>D1 (1 ~ 25fps)</b>
Sub stream 2	<b>720P (1 ~ 25fps)</b>
Mirror	<b>On / Off</b>

### VIDEO ANALYSIS

Tipo de detección	<b>Analítica con clasificación humano/vehículo/vehículo no motorizado en cruce de línea/área</b>
Funciones IA	<b>Conteo de personas, mapa de calor, detección facial</b>
Crossing line	<b>Yes</b>
Intrusion	<b>Yes</b>
Face detection	<b>Yes</b>
Classification Human / vehicle	<b>Si</b>
SMD	<b>Yes</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>5.2W</b>

### NETWORK FEATURES

IP connection	<b>1 RJ45 (10M / 100M)</b>
ONVIF	<b>Yes, G type</b>
Maximum number of users	<b>20 users</b>
Web browser	<b>Explorer / Chrome / Firefox</b>
Management software	<b>Smart PSS / ConfigTool (ambos en red local)</b>
Mobile devices	<b>Android / IOS (Apple)</b>
Network disconnection	<b>Yes</b>
Conflict of IP addresses	<b>Yes</b>

### IMAGE

Sensor	<b>CMOS ®</b>
Resolución sensor	<b>2880 x 1620</b>
Sensor Size	<b>1/2.7'</b>
Electronic shutter speed	<b>1/3 ~ 1/100000s</b>
Minimum lighting	<b>Color: 0.002Lux / B/W: 0.0002Lux</b>
Ratio S / N	<b>More than 56dB</b>

### NIGHT VISION

Night vision distance	<b>40 m</b>
Type of night vision	<b>IR</b>
IR ON/Off	<b>Automatic / Manual</b>
Starlight	<b>Yes</b>

### LENS

Lens Type	<b>Fix</b>
Focal distance	<b>2.8 mm</b>
Maximum diaphragm opening	<b>F/1.6</b>
Angle of View	<b>111°</b>

### AMBIENT

Operating temperature	<b>-40 °C ~ 60 °C</b>
Degree of protection	<b>IP67</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>

# technical datasheet

Amperage	<b>440mA</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

## DISTANCE DORI

Detect	<b>60</b>
Observe	<b>24 m</b>
Recognize	<b>12 m</b>
Identify	<b>6 m</b>

## MATERIAL AND DIMENSIONS

Dimensions	<b>110 x 122 (Ø) mm</b>
Material	<b>Metal</b>
Net weight	<b>610 g</b>
Weight with packaging	<b>730 g</b>

## STORAGE

MicroSD-Card	<b>Up to 256Gb</b>
Storage Systems	<b>FTP / Micro SD</b>
Storage anomaly	<b>Yes</b>

## SYSTEM (CAMERAS)

Ram memory	<b>128 MB</b>
ROM memory	<b>256 MB</b>

## SPECS AND FEATURES

Serie	<b>Serie 3</b>
Technology	<b>IP</b>
Type of camera	<b>Minidome</b>

## AUDIO(CAMERAS)

Built in microphone	<b>Yes</b>
Audio compression	<b>G.711A / G.711U / G.726 / G.726ASF</b>

## AXES

Motion	<b>3-Axis</b>
--------	---------------

