

43



MOVOK

Bullet ip camera of 5 megapixels and optical zoom lens

VK-IPC-B351-ZAS-TI

VIDEO (CAMERAS)

Video Resolution	5 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (140 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	5Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	67 m
Detect (Closed Lens)	239 m
Observe (Open lens)	27 m
Observe (Closed lens)	95 m
Recognize (Open lens)	13 m
Recognize (Closed lens)	46 m
Identify (Open lens)	7 m
Identify (Closed lens)	23 m

NIGHT VISION

Night vision distance	50 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
Starlight	Yes
White light	Si

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
Funciones IA	Conteo de personas, mapa de calor, detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Heatmap	Yes
People counting	Yes
Classification Human / vehicle	Yes
SMD	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	550mA
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Dimensions	244 x 77 x 76 mm
Material	Metal
Net weight	810 g

technical datasheet

White light distance	50 m
----------------------	------

IMAGE

Sensor	CMOS ®
Sensor resolution	2880 x 1620
Sensor Size	1/2.7"
Electronic shutter speed	1/3 ~ 1/1000000s
Minimum lighting	0.001Lux

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 13.5 mm
Maximum diaphragm opening	F/1.0
Angle of View	99° ~ 28°

GENERAL INFORMATION

Serie	Serie 3
Technology	IP
Type of camera	Bullet

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	FTP / Micro SD
Storage anomaly	Yes

AXES

Motion	3-Axis
--------	--------

Weight with packaging	950 g
-----------------------	-------

Color	White
-------	-------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

AUDIO(CAMERAS)

Built in microphone	Yes
Built in speaker	Yes
Audio compression	G.711A / G.711U / G.726 / G.726ASF

SYSTEM (CAMERAS)

Ram memory	128 MB
ROM memory	256 MB

TIOC

Siren	Yes
Light	White