



AJAX

Wired volumetric detector

MOTIONCAM-PHOD-FIBRA-B

TECHNICAL SPECIFICATIONS

Compatibility	Ajax Fibra panels
LED indicators	Yes
Tamper	Dual
Tiempo de intervalo para la conexión con el receptor	12 ~ 300 sec
Connection type	BUS
Protection against false alarms	Yes, algorithmic analysis
Transmission distance	Up to 2000 m

DETECTION

Detector type	Wired
Installation height	2.4 m
Angle detection	88.5° Horizontal / 80° Vertical
Detection distance	12 m
Detection speed	0,3 m/s ~ 2 m/s
Pets immunity	Up to 20 kg and 50 cm
Detection technology	Volumetric

VERIFICACIÓN FOTOGRÁFICA

Picture quality	640 x 480 / 320 x 240 (default) / 160 x 120
Reception time of a photo	7 s (160 x 120) / 9 s (320 x 240) / 20 s (640 x 480)
Series images	1 - 5 images
Foto bajo demanda (PhOD)	Yes

SENSOR

Type of sensor	PIR
Sensitivity adjustment	Sí
Digital temperature compensation	Yes

MATERIAL AND DIMENSIONS

Dimensions	135 x 70 x 66 mm
Material	Plastic
Net weight	160 g
Weight with packaging	200 g
Color	Black

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Degree of protection	IP50
Use	Indoor
Maximum humidity	75%

POWER CONSUMPTION

Power mode	DC (via Hub Hybrid BUS)
Voltage	24V
Battery support	Included

