




## Módulo para integración de dispositivos de terceros en sistemas

### TRANSMITTER-FIBRA



#### POWER CONSUMPTION

|                     |                         |
|---------------------|-------------------------|
| Power mode          | DC (via Hub Hybrid BUS) |
| Voltage             | 7V ~ 30V                |
| Amperage            | 200mA                   |
| Power output        | DC 10.5V ~ 15V          |
| Maximum consumption | 50mA                    |

#### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -25 °C ~ 50 °C |
| Use                   | Indoor         |
| Maximum humidity      | 75%            |

#### ESPECIFICACIONES TÉCNICAS

|                       |                             |
|-----------------------|-----------------------------|
| Compatibility         | Ajax Fibra panels           |
| Connection type       | NC / NO / EOL / 2EOL / 3EOL |
| Transmission distance | Up to 2000 m                |

#### ZONES

|                         |   |
|-------------------------|---|
| Maximum number of zones | 2 |
|-------------------------|---|

#### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Dimensions            | 40 x 15 x 12.2 mm |
| Net weight            | 5 g               |
| Weight with packaging | 20 g              |

#### CERTIFICATION

|           |         |
|-----------|---------|
| Grade     | 3       |
| Normative | EN50131 |

#### GENERAL INFORMATION

|      |                                                                 |
|------|-----------------------------------------------------------------|
| Type | Módulo para integración de dispositivos de terceros en sistemas |
|------|-----------------------------------------------------------------|

