



HIKVISION
accessories

Access control indoor-outdoor
with keyboard / card mifare /
desfire 13.56mhz

DS-K1T502DBWX

INPUTS/OUTPUTS

Alarm input	1
RS485	1
Door sensor	1
Exit button	1
Blocking entry	1
Alarm output	1

IDENTIFICATION

Mode	Keyboard / Card
Type of card	MIFARE 13.56MHz
Maximum reading distance	3 cm
Card reading time	menos de 1 s
Number of cards	100000
NUmber of register	300000

AMBIENT

Operating temperature	-40 °C ~ 70 °C
Degree of protection	IP65
Anti vandal	IK09
Use	Indoor-outdoor

FEATURES

Integrated controller	Sí
Tamper	Sí
Integrated microphone	Yes
Integrated speaker	Yes

GENERAL INFORMATION

Control type	Access control
--------------	-----------------------

POWER CONSUMPTION

Power mode	DC / AC
Voltage	12V / 24V
Consumption (w)	12W
Amperage	1000mA

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	177 x 81 x 26.1 mm
Net weight	620 g
Weight with packaging	1030 g

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	Linux
Memory	256 MB RAM / 4096 MB ROM
CPU	960 MHz
SD card	Up to 256 GB

COMMUNICATION

Wi-Fi	Sí
Bluetooth	Yes
Mode	Wiegand / RS485

