



HIKVISION®

Minidome ip camera of 4 megapixels and fix lens

DS-2CD1347G2H-LIU

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx (1 ~ 20fps) / 1080P / 720P (1 ~ 25fps)
Sub stream	720P / 640 x 480 / 640 x 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6W
Amperage	500mA

NIGHT VISION

Night vision distance	30 m
Type of night vision	Dual light (IR+Luz blanca)
Number of LEDs	1
IR ON/Off	Automatic / Manual
White light	1
Wavelength	850 nm
Smart Hybrid Light	Yes (switches from IR to colour with human detection)

IMAGE

Sensor	CMOS ®
Sensor resolution	2560 x 1440
Sensor Size	1/3'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.001Lux
Ratio S / N	Más de 52dB

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.0
Angle of View	96°
Filtro IR	Sí

AUDIO(CAMERAS)

Built in microphone	Yes
Audio compression	G.711A / G.711U / G.722.1 / G.726 / AAC-LC / MP2L2 / PCM
Noise filter	SI
Sampling frequency	8kHz / 16kHz
Bit rate	64 Kbps (G.711) / 16 Kbps (G.722.1 / G.726) / 16 ~ 64 Kbps (AAC) / 32 ~ 160 Kbps (MP2L2)

MATERIAL AND DIMENSIONS

Dimensions	93 x 110 (Ø) mm
Material	Metal and plastic

technical datasheet

PoE power	Yes
-----------	-----

Type PoE	PoE 802.3af
----------	-------------

AMBIENT

Operating temperature	-30 °C ~ 60 °C
-----------------------	----------------

Degree of protection	IP67
----------------------	------

Use	Indoor-outdoor
-----	----------------

Maximum humidity	95%
------------------	-----

DISTANCE DORI

Detect	63 m
--------	------

Observe	25 m
---------	------

Recognize	12 m
-----------	------

Identify	6 m
----------	-----

GENERAL INFORMATION

Serie	ColorVu
-------	---------

Technology	IP
------------	----

Type of camera	Minidome
----------------	----------

STORAGE

Storage Systems	FTP
-----------------	-----

Net weight	420 g
------------	-------

Weight with packaging	660 g
-----------------------	-------

VIDEO ANALYSIS

Detection type	Advanced detection (person/vehicle classification)
----------------	---

Motion detection	Yes
------------------	-----

Video Tamper	Sí
--------------	----

Classification Human / vehicle	Yes
-----------------------------------	-----

AXES

Motion	3-Axis
--------	--------

