



HIKVISION
accessories

Wi-Fi 5 access point DS-3WF0FA-5AC/O

WI-FI

| | |
|-----------------------|---|
| Wi-Fi standard | IEEE802.11 a / n / ac |
| Frequency range | 5.15 GHz ~ 5.25 GHz / 5.25 GHz ~ 5.35 GHz / 5.47 GHz ~ 5.725 GHz / 5.725 GHz ~ 5.85 GHz |
| Broadband channel | 20 / 40 / 80 MHz |
| Security | WPA2-PSK |
| Speed | 867Mbps |
| Transmission distance | 1000 m |
| Angle | Horizontal 360° / Vertical 8° |
| Antenna | 8dBi |
| MIMO | 2 x 2 |

POWER CONSUMPTION

| | |
|-----------------|-------------|
| Consumption (w) | 4.5W |
| PoE power | Yes |
| Type PoE | PoE 802.3af |

TECHNICAL CHARACTERISTICS

| | |
|---------------|-----|
| LED indicator | Yes |
| DIP Switch | Yes |

ETHERNET PORTS

| | |
|-----------------|---|
| 10 / 100 / 1000 | 2 |
|-----------------|---|

AMBIENT

| | |
|-----------------------|----------------|
| Operating temperature | -30 °C ~ 60 °C |
| Degree of protection | IP55 |
| Use | Indoor-outdoor |
| Maximum humidity | 95% |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|-------------------------|
| Dimensions | 198.4 x 103.6 x 58.3 mm |
| Net weight | 300 g |
| Weight with packaging | 3500 g |

INPUTS/OUTPUTS

| | |
|------|------------------------|
| RJ45 | 1 x PoE / LAN, 1 x LAN |
|------|------------------------|

