



## MOVOK

Minidome ip camera of 4 megapixels and fix lens

VK-IPC-T241-LI

### VIDEO (CAMERAS)

Resolución vídeo	<b>4 Megapixels</b>
BLC	<b>Yes</b>
HLC	<b>Yes</b>
3D-NR	<b>Yes</b>
AGC	<b>Yes</b>
AWB	<b>Yes</b>
WDR	<b>DWDR</b>
Images per second	<b>25fps</b>
Video output	<b>RJ45</b>
Day / night mode	<b>Colour</b>
Privacy mask	<b>Up to 4 zones</b>
Type of Codex	<b>CBR / VBR</b>
Bit rate	<b>3Kbps ~ 20480Kbps</b>
Compression	<b>H.265 / H.264</b>
Main stream	<b>4Mpx (1 ~ 25fps)</b>
Sub stream	<b>D1 (1 ~ 25fps)</b>
Sub stream 2	<b>720P (1 ~ 25fps)</b>
Mirror	<b>On / Off</b>

### NIGHT VISION

Night vision distance	<b>30 m</b>
Tipo de visión nocturna	<b>Dual light (IR+Luz blanca)</b>
IR ON/Off	<b>Automatic / Manual</b>
White light distance	<b>30 m</b>
White light	<b>Sí</b>
Smart Dual Illumination	<b>Yes (switches from IR to colour with human detection)</b>

### NETWORK FEATURES

IP connection	<b>1 RJ45 (10M / 100M)</b>
ONVIF	<b>Yes, G type</b>
Web browser	<b>Explorer</b>
Management software	<b>Smart PSS / ConfigTool (ambos en red local)</b>

### IMAGE

Sensor	<b>CMOS ®</b>
Resolución sensor	<b>2688 x 1520</b>
Sensor Size	<b>1/2.7'</b>
Electronic shutter speed	<b>1/3 ~ 1/100000s</b>
Minimum lighting	<b>0.006Lux</b>
Ratio S / N	<b>More than 56dB</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>3W</b>
Amperage	<b>250mA</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

### VIDEO ANALYSIS

Tipo de deteccion	<b>Analitica con clasificacion humano/vehiculo/vehiculo no motorizado en cruce de línea/área</b>
Crossing line	<b>Yes</b>
Intrusion	<b>Yes</b>
Motion detection	<b>Yes (4 areas)</b>
Classification Human / vehicle	<b>Sí</b>
SMD	<b>Yes</b>

### LENS

Lens Type	<b>Fix</b>
Focal distance	<b>2.8 mm</b>
Maximum diaphragm opening	<b>F/1.6</b>
Angle of View	<b>107°</b>

### DISTANCE DORI

Detect	<b>58 m</b>
Observe	<b>23 m</b>
Recognize	<b>12 m</b>
Identify	<b>6 m</b>

# technical datasheet

Network disconnection	<b>Yes</b>
-----------------------	------------

Conflict of IP addresses	<b>Yes</b>
--------------------------	------------

## MATERIAL AND DIMENSIONS

Dimensions	<b>97 x 110 (Ø) mm</b>
------------	------------------------

Material	<b>Metal and plastic</b>
----------	--------------------------

Net weight	<b>350 g</b>
------------	--------------

Weight with packaging	<b>480 g</b>
-----------------------	--------------

Color	<b>White</b>
-------	--------------

## AMBIENT

Operating temperature	<b>-30 °C ~ 60 °C</b>
-----------------------	-----------------------

Degree of protection	<b>IP67</b>
----------------------	-------------

Use	<b>Indoor-outdoor</b>
-----	-----------------------

Maximum humidity	<b>95%</b>
------------------	------------

## AXES

Motion	<b>3-Axis</b>
--------	---------------

## SPECS AND FEATURES

Technology	<b>IP</b>
------------	-----------

Type of camera	<b>Minidome</b>
----------------	-----------------

Serie	<b>Serie 2</b>
-------	----------------

## STORAGE

Storage Systems	<b>FTP</b>
-----------------	------------

