



MOVOK

Minidome ip camera of 4 megapixels and optical zoom lens

VK-IPC-T241-ZAS-LI-B

VIDEO (CAMERAS)

Video Resolution	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 20480Kbps
Compression	H.265 / H.264
Main stream	4Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Sub stream 2	720P (1 ~ 25fps)
Mirror	On / Off

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Network disconnection	Yes
Conflict of IP addresses	Yes

NIGHT VISION

Night vision distance	40 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
White light	Si

DISTANCE DORI

Detect (Open lens)	62 m
Detect (Closed Lens)	220 m
Observe (Open lens)	25 m
Observe (Closed lens)	84 m
Recognize (Open lens)	12 m
Recognize (Closed lens)	44 m
Identify (Open lens)	6 m
Identify (Closed lens)	22 m

IMAGE

Sensor	CMOS ®
Sensor resolution	2688 x 1520
Sensor Size	1/2.7'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.006Lux
Ratio S / N	More than 56dB

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	550mA
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Dimensions	110 x 122 (Ø) mm
Material	Metal
Net weight	630 g
Weight with packaging	780 g
Color	Black

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 13.5 mm
Maximum diaphragm opening	F/1.6

technical datasheet

White light distance	40 m
----------------------	------

Smart Dual Illumination	Yes (switches from IR to colour with human detection)
-------------------------	---

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
----------------	---

Crossing line	Yes
---------------	-----

Intrusion	Yes
-----------	-----

Motion detection	Yes (4 areas)
------------------	---------------

Classification Human / vehicle	Yes
--------------------------------	-----

SMD	Yes
-----	-----

AMBIENT

Operating temperature	-30 °C ~ 60 °C
-----------------------	----------------

Degree of protection	IP67
----------------------	------

Use	Indoor-outdoor
-----	----------------

Maximum humidity	95%
------------------	-----

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	FTP / Micro SD
-----------------	----------------

Storage anomaly	Yes
-----------------	-----

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Angle of View	99° ~ 28°
---------------	-----------

GENERAL INFORMATION

Serie	Serie 2
-------	---------

Technology	IP
------------	----

Type of camera	Minidome
----------------	----------

AXES

Motion	3-Axis
--------	--------

