



2 wires / ip of surface / embed video intercom

VTO3222E-P

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af / PoE+ 802.3at
Standby consumption	5W
Consumption On	7W
Power output	1 x 12V DC / 600mA

INPUTS/OUTPUTS

Wiegand	Yes
Alarm input	1
RS485	1
Exit button	1
Blocking entry	1
Alarm output	1
Bell	1
RJ45	1

IDENTIFICATION

Mode	Keyboard / Card
Type of card	MIFARE 13.56MHz
Maximum reading distance	3 cm
Number of cards	10000
Number of users	5000
Identificación remota	Sí
Multi-factor authentication	Yes

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711A/G.711U/PCM

OPENING

Call elements	Simple buttons
---------------	----------------

CAMERA

Resolution	2 Mpx
Sensor	CMOS
Sensor size	1/2.9"
Horizontal viewing angle	140°
Diagonal angle of view	160°
Night vision	Yes, white light
Day / Night	Mechanical
Video compression	H.265

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	200 x 98 x 35.4 mm
Net weight	500 g
Weight with packaging	690 g

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
Memory slot	SD up to 256Gb
Led indicator	Sí, 3
Message recording if no response	Yes (SD card required)

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

IP connection	10M/100Mbps
---------------	-------------

technical datasheet

Proximity reader **Yes**

Mode **Card / Password / Remote**

GENERAL INFORMATION

Technology **2 Wires / IP**

