



26 ports cloud switch with 24 PoE ports

DS-3E1526P-SI



REMOTE MANAGEMENT

Software	Hik Partner Pro
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

CHARACTERISTICS (SWITCH)

Data rate supported	56 Gbps
Packet redirection speed	41.7 Mpps
VLAN	802.1Q
Maximum transmission distance	300 m
Buffer Memory	4.1 Mb
PoE Watchdog	Yes
Spanning Tree	Yes, STP / RSTP
QoS	Yes
Port Aggregation	LACP / Static aggregation (max. 8 groups)

AMBIENT

Operating temperature	0 °C ~ 45 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

NET STANDARD

IEEE802.3af	Si
IEEE802.3at	Si

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	400W
Amperage	6300mA
Standby consumption	30W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	370W

MATERIAL AND DIMENSIONS

Installation	Rack
Dimensions	440 x 221 x 44 mm
Material	Metal
Net weight	2980 g
Weight with packaging	3530 g

ETHERNET PORTS

POE ports	24
Fiber port	2 x 1000
POE Ports Speed	10 / 100 / 1000
Number of Ethernet ports	26

SYSTEM (SWITCH)

MAC address table	8K
-------------------	-----------

