



HIKVISION
intrusion

Wired volumetric detector

DS-PDTT15AM-LM

DETECTION

Detector type	Wired
Installation height	0.8 m ~ 1.2 m
Angle detection	90° / 180°
Detection distance	15 m
Detection method	Infrared and microwave
Detection speed	0,3 m/s ~ 2 m/s
Detection zones	92
Pets immunity	Up to 40 Kg
Antimasking	Yes
Sway Recognition™ (excludes vegetation)	Yes

SENSOR

Type of sensor	PIR and microwave
Sensitivity adjustment	Si
High sensitivity	Si
Low sensitivity	Si
Microwave	24GHz
Digital temperature compensation	Yes

TECHNICAL SPECIFICATIONS

LED indicators	Yes
LED colors	Red / Green / Yellow / Blue
Tamper	Dual
EOL resistors (end of line)	Si

CERTIFICATION

Grade	2
Environmental class	IV

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Standby consumption	30mA
Consumption On	220mA

AMBIENT

Operating temperature	-25 °C ~ 60 °C
Degree of protection	IP65
Use	Outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Dimensions	202 x 75 x 73 mm
Net weight	360 g
Weight with packaging	510 g

INPUTS/OUTPUTS

Alarm output	NC
--------------	-----------

