



HIKVISION
intrusion

Wired volumetric detector

DS-PD501PC12

DETECTION

Detector type	Wired
Installation height	1.8 m ~ 2.4 m
Angle detection	90°
Detection distance	12 m
Detection speed	0,3 m/s ~ 2 m/s
Detection zones	84
Pets immunity	Up to 24 kg

POWER CONSUMPTION

Power mode	DC (via BUS)
Voltage	12V
Amperage	100mA
Standby consumption	70mA

VERIFICACIÓN FOTOGRÁFICA

Sensor	CMOS®
Angle of view	109° horizontal / 60° vertical
Picture quality	1920 x 1080 / 1280 x 720 / 640 x 480
Series	3 (1920 x 1080) / 6 (1280 x 720) / 10 (640 x 480)

SENSOR

Type of sensor	PIR
PIR sensitivity	Selectable LO / MID / HI
Digital temperature compensation	Yes

GENERAL INFORMATION

Serie	AXPRO
-------	--------------

MATERIAL AND DIMENSIONS

Installation	Wall / ceiling
Dimensions	73 x 130.5 x 56.7 mm
Net weight	195 g
Weight with packaging	240 g

AMBIENT

Operating temperature	-10 °C ~ 50 °C
Use	Indoor
Maximum humidity	90%

TECHNICAL SPECIFICATIONS

Compatibility	Hikvision panels
Tamper	Dual
Connection type	BUS

CERTIFICATION

Grade	2
Environmental class	II

