

Milesight



IP recorder of 16 channel and 12 mpx resolution

MS-N7016-G

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	160Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Recording mode	Continuous / Event (motion detection, alarm, VCA, Smart analysis)
Audio compression	G.711 / G.722 / G.726 / AAC
Audio sampling frequency	8KHz / 16KHz
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / D1 / VGA / CIF / QCIF
ANR (Redundant Recording in SD)	Si
Output bandwidth	160Mbps

INTELLIGENT VIDEO SYSTEM

Abandoned object	Yes
missing object	Yes
Line crossing	Yes
Face detection	Yes
People counting	Si
Motion detection	Yes
Video Tamper	Yes
Loitering detection	Yes
ANPR	Yes

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
VGA resolution	1080P

STORAGE

Number of supported hard drives	4
---------------------------------	----------

MATERIAL AND DIMENSIONS

Installation	Rack
Dimensions	440 x 320 x 66.8 mm
Material	Metal
Net weight	4100 g
Weight with packaging	5500 g
Chassis	1.5U

INPUTS/OUTPUTS

Alarm input	16
USB 2.0	2
USB 3.0	1
RS232	1
RS485	1
Alarm output	4

NETWORK FEATURES

Number of ports RJ45	2
Speed RJ45	10 / 100 / 1000 Mbps
ONVIF	Yes
Software	Milesight CMS

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	15W

GENERAL INFORMATION

Serie	4K PRO Series
Technology	IP

VIDEO

IP Channels	16
-------------	-----------

technical datasheet

Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"
Raid	0 / 1 / 5 / 6 / 10

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

AUDIO

Audio Inputs	1
Audio Outputs	1

